

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (previously presented) A dental articulating system configured to duplicate at least a portion of a patient's mouth for use in producing a dental prosthesis, the device comprising:
 - a) a pair of trays, pivotally coupled together;
 - b) a plurality of registration pin holes, formed in at least one of the trays;
 - c) at least one indentation, formed in at least one of the trays at a bottom of at least one of the plurality of registration pin holes, and sized to receive a tip of a finger or thumb;
 - d) a thin membrane, disposed across the registration pin holes between the registration pin holes and the indentation, configured to close off the registration pin holes and resist dental casting material from substantially filling the registration pin holes; and
 - e) at least one registration pin, disposable in at least one of the plurality of registration pin holes, the thin membrane being breakable by the registration pin inserted into the registration pin hole with the registration pin being extendable through the thin membrane and into the indentation.
2. (canceled)
3. (currently amended) A system in accordance with claim 1, wherein the thin membrane formed integrally with ~~with~~ one another and of the same material.
4. (original) A system in accordance with claim 1, wherein the thin membrane is separately formed from the tray and attached to the tray.
5. (canceled)

6. (canceled)
7. (canceled)
8. (original) A system in accordance with claim 1, further comprising:
registration struts, formed in at least one of the trays, having a hexagonal cross section.
9. (original) A system in accordance with claim 1, further comprising:
a trough formed in at least one of the trays by a perimeter wall, the perimeter wall having a wavy profile with a plurality of arcuate indentations.
10. (original) A system in accordance with claim 1, further comprising:
a hinge, integrally formed with the trays and positioned between the trays, including:
i) a pivot axle, associated with one of the trays;
ii) a shoulder, extending at least partially around the pivot axle and creating two axle portions extending on each side of the shoulder; and
iii) a pair of fingers, associated with another of the trays, pivotally positioned on opposite sides of the pivot axle and on opposite sides of the shoulder and separated by both the axle and the shoulder.
11. (currently amended) A method for forming a dental model, comprising the steps of:
a) pressing a registration pin through a thin membrane extending across a plurality of registration pin holes on a working tray of a dental articulator so that the registration pin breaks the thin membrane and extends through the thin membrane;
b) forming a prepped model of a prepped tooth by disposing dental casting material over the registration pin on the working tray of the dental articulator while the registration pin remains in the registration pin hole, the prepped model of the prepped

tooth to receive a dental prosthesis; ~~and~~

c) maintaining a position of the registration pin in the registration pin hole through the thin membrane while the prepped model of the prepped tooth is formed; and

d) e)-forming an opposing model of an opposing tooth on an opposing tray of the dental articulator, the opposing model of the opposing tooth opposing the prepped tooth.

12. (original) A method in accordance with claim 11, further comprising the step of:
segmenting the prepped model on sides corresponding to the prepped tooth to form a prosthesis die.

13. (previously presented) A method in accordance with claim 11, wherein the step of forming the prepped model further includes the step of:

disposing dental casting material over the registration pin holes in the working tray with the thin membrane formed integrally with the working tray and extending across the registration pin holes to resist dental casting material from substantially filling the registration pin holes.

14. (original) A method in accordance with claim 11, wherein the step of pressing the registration pin through the thin membrane further includes the step of:

pressing the registration pin through a thin membrane extending across the registration pin hole near a bottom of the registration pin hole.

15. (currently amended) A method in accordance with claim 11, wherein the step of pressing the registration pin through the thin membrane further includes the step of:

pressing the registration pin through the thin membrane disposed at a die receiving surface of the working tray.

16. (original) A method in accordance with claim 11, further comprising the step of:
pushing a thumb or finger into a thumb indentation positioned at a bottom of a

registration pin hole to push a registration pin out of the registration pin hole.

17. (original) A method in accordance with claim 11, wherein the step of forming the prepped model further includes the step of:

disposing dental casting material around registration struts in at least one of the trays, the registration struts having a hexagonal cross section.

18. (original) A method in accordance with claim 11, wherein the step of forming the prepped model further includes the step of:

disposing dental casting material in at least one of the trays with a trough formed by a perimeter wall, the perimeter wall having a wavy profile with a plurality of arcuate indentations.

19. (previously presented) A method in accordance with claim 11, further comprising the step of:

pivoting the working and opposing trays about a hinge integrally formed with the trays, the hinge including a first portion with a shoulder circumscribing an axle and a second portion with opposing fingers movably disposed on opposite sides of the axle and on opposite sides of the shoulder.

20. (previously presented) A method in accordance with claim 11, wherein the steps of forming the prepped and opposing models further includes the steps of:

a) obtaining an impression of at least some of a patient's teeth, the impression including a prepped side with an impression of the prepped tooth to receive the dental prosthesis, and an opposing side with an impression of the opposing tooth opposing the prepped tooth;

b) introducing dental casting material between the opposing tray and the opposing side of the impression to form the opposing model of the opposing tooth;

c) introducing dental casting material between the working tray and the prepped

side of the impression to form the prepped model of the prepped tooth; and

d) removing the impression from the dental articulator leaving the opposing and the prepped models on respective opposing and working trays.

21. (currently amended) A method for forming a dental model, comprising the steps of:

a) obtaining an impression of at least some of a patient's teeth, the impression including a prepped side with an impression of a prepped tooth to receive a dental prosthesis, and an opposing side with an impression of an opposing tooth opposing the prepped tooth;

b) obtaining a dental articulator with opposing and working trays pivotally coupled together and a thin membrane extending across a plurality of registration pin holes in the working tray;

c) disposing dental casting material on the opposing tray and in the opposing side of the impression;

d) disposing the opposing side of the impression over the opposing tray so that dental casting material extends therebetween and forms an opposing model of the opposing tooth;

e) positioning at least one registration pin in the plurality of registration pin holes in the working tray at a location corresponding to the prepped tooth;

f) pressing the at least one registration pin through the thin membrane extending across the at least one of the plurality of registration pin holes;

g) disposing dental casting material in the prepped side of the impression and on the working tray with the at least one registration pin remaining in the at least one of the plurality of registration pin holes to resist dental casting material from entering the plurality of registration pin holes;

h) maintaining a position of the at least one registration pin in the registration pin hole through the thin membrane while the dental casting material is disposed on a surface of the working tray and over a head of the at least one registration pin;

i) ~~h~~-disposing the working tray over the prepped side of the impression so that the

dental casting material extends therebetween and forms a prepped model of the prepped tooth; and

j) ~~i~~ removing the impression from the dental articulator.

22. (original) A method in accordance with claim 21, further comprising the step of:
segmenting the dental casting material of the prepped model on sides
corresponding to the prepped tooth to form a prosthesis die.

23. (previously presented) A method in accordance with claim 21, wherein the step of
introducing dental casting material further includes the step of:

disposing the dental casting material over the registration pin holes with the thin
membrane being integrally formed with the working tray and extending across the
registration pin holes to resist the dental casting material from substantially filling the
registration pin holes.

24. (original) A method in accordance with claim 21, wherein the step of pressing the
registration pin through the thin membrane further includes the step of:

pressing the registration pin through the thin membrane extending across the
registration pin hole near a bottom of the registration pin hole.

25. (previously presented) A method in accordance with claim 21, wherein the step of
pressing the registration pin through the thin membrane further includes the step of:

pressing the registration pin through the thin membrane disposed at a die
receiving surface of the working tray.

26. (original) A method in accordance with claim 21, wherein the step of introducing
dental casting material further includes the step of:

disposing dental casting material around registration struts in at least one of the
trays, the registration struts having a hexagonal cross section.

27. (original) A method in accordance with claim 21, wherein the step of introducing dental casting material further includes the step of:

disposing dental casting material in a trough formed by a perimeter wall, the perimeter wall having a wavy profile with a plurality of arcuate indentations.

28. (original) A method in accordance with claim 21, further comprising the step of:

pivoting the lower and upper trays about a hinge integrally formed with the trays, the hinge including a first portion with a shoulder circumscribing an axle and a second portion with opposing fingers movably disposed on opposite sides of the axle and on opposite sides of the shoulder.

29. (canceled)

30. (canceled)

31. (canceled).

32. (canceled).

33. (currently amended) A method for forming a dental model, comprising the steps of:

a) obtaining an impression of at least some of a patient's teeth, the impression including a prepped side with an impression of the prepped tooth to receive the dental prosthesis, and an opposing side with an impression of the opposing tooth opposing the prepped tooth;

b) pressing a registration pin through a thin membrane extending across a plurality of registration pin holes on a working tray of a dental articulator so that the registration pin breaks the thin membrane and extends through the thin membrane;

c) introducing dental casting material on ~~between~~ the working tray ~~and the~~

~~prepped side of the impression,~~ and over the registration pin while the registration pin remains in the registration pin hole, to form a prepped model of a prepped tooth on the working tray of the dental articulator, the prepped model of the prepped tooth to receive a dental prosthesis;

d) introducing dental casting material between an opposing tray and the opposing side of the impression to form an opposing model of an opposing tooth on an opposite tray of the dental articulator, the opposing model of the opposing tooth opposing the prepped tooth.

34. (canceled).

35. (canceled).

36. (previously presented) A system in accordance with claim 1, wherein the at least one indentation further includes a plurality of indentations, each associated with one of the plurality of registration pin holes.

37. (previously presented) A system in accordance with claim 1, wherein the at least one indentation is formed in the tray separate from a perimeter wall of the tray.

38. (previously presented) A method in accordance with claim 11, wherein the step of forming the prepped model further includes the step of:

disposing dental casting material over the registration pin holes in the working tray with the thin membrane formed separately from the working tray and attached to the working tray.

39. (previously presented) A method in accordance with claim 21, wherein the step of forming the prepped model further includes the step of:

disposing dental casting material over the registration pin holes in the working

tray with the thin membrane formed separately from the working tray and attached to the working tray.

40. (new) A dental articulating system configured to duplicate at least a portion of a patient's mouth for use in producing a dental prosthesis, the device comprising:

- a) a pair of trays, pivotally coupled together;
- b) a plurality of registration pin holes, formed in at least one of the trays;
- c) a thin membrane, disposed across the registration pin holes below a surface of the at least one of the trays, configured to close off the registration pin holes and resist dental casting material from substantially filling the registration pin holes;
- d) at least one registration pin, disposable in at least one of the plurality of registration pin holes, the thin membrane being breakable by the registration pin inserted into the registration pin hole with the registration pin being extendable through the thin membrane; and
- e) wherein each of the pin holes comprises a substantially round elongate chamber having a depth greater than a width, and wherein the thin membrane creates an air pocket in the elongate chamber when casting material is poured to resist dental casting material from substantially filling the elongate chamber.

41. (new) A dental articulating system configured to duplicate at least a portion of a patient's mouth for use in producing a dental prosthesis, the device comprising:

- a) a pair of trays, pivotally coupled together;
- b) a plurality of registration pin holes, formed in at least one of the trays, each of the registration pin holes comprising a substantially round elongate chamber having a depth greater than a width;
- c) a thin membrane, disposed across the registration pin holes, configured to close off the registration pin holes and resist dental casting material from substantially filling the registration pin holes; and
- d) at least one registration pin, disposable in at least one of the plurality of

registration pin holes, the thin membrane being breakable by the registration pin inserted into the registration pin hole with the registration pin being extendable through the thin membrane.